

Stenlim Pro

Adhesive intended for bricks and similar materials

Product description:

Single-component PU-adhesive for fastening construction blocks and stones during construction works. Compared to mortar, Stenlim Pro facilitates carrying out the masonry works faster, thereby leaving the work environment dust free and using a foam gun as the only tool. Stenlim Pro forms a strong adhesive joint within just 30 minutes.

Applications:

Used for fastening construction blocks of non-bearing walls. Is intended for bricks, blocks, porous concrete, Leca, etc. but works equally well with most metals and wood.

Technical data:

Type	Polyurethane
Curing system	Moisture activated
Consistency	Expanding foam
Color	Yellow
Packaging [ml]	400, 750
Solids content	100%
Skin time/open time [min]	8-15 min
Cure time [h]	24, (72 at 5 °C, 50 % RH)
Application temperature (wet) [C°]	+5 ÷ +25
Application temperature (cured) [C°]	-40 ÷ +90
Shelf life cool & dry [months]**	12
Storage temperature [°C]	+5 - +30
Flashpoint of cured adhesive [°C]	400

All values at 23 ° / 50 % RH, unless otherwise indicated

** Best before labeled packaging for products with bag in box applies to unopened bag.

Instruction/Application:

Follow the directions on the package. Ambient and material temperature should be 5°C ÷ +25°C. The cartridge should be at room temperature. Make sure that the surfaces are clean, free from dust/particles and grease/oil before applying the adhesive. If necessary, clean thoroughly. Use alcohol, acetone or other suitable volatile agent that leaves no residues. Nafta can leave a layer of oil that can give adhesion problems.

if light materials are being joined. Clean away any excess adhesive immediately.

Resistance to aging:

Excellent, the product is fully waterproof.

Cleaning:

Wet product can be cleaned with ESSVE RENGÖRINGSDUK, ESSVE RENGÖRINGSSPRAY or similar products, cured product can only be removed mechanically.

Storage:

Best stored dark, cool and dry (5-25°C). Store upright.

Safety:

See separate safety data sheet.

Notes:

All information in this document is given in accordance with known facts and information at the time of writing. The information is subject to change without further notification. The document is updated continuously in conjunction with regular revision or in the event of major-specific technical changes.

All advice given by ESSVE should only be seen as indicative and does not mean that ESSVE can be held responsible for the advice provided. It is always the customer's responsibility, at his/her own risk, to decide on the choice of product, usage, applications, etc. The Supplier's advice is only a part of the customer's decision making data.